

TXL-BOY-014 / 27 October 2026 · One-year manufacturer warranty

Horizontal Padder

Used for squeezing operations after dyeing and washing of fabrics. It has horizontally arranged cylinders 350 mm or 500 mm wide with 70 shore hardness. Fabric passage speed is adjustable between 1 and 40 m/min and squeezing pressure between 2 and 6 bar. A balance adjustment system provides equal pressure, with safety locks between the rollers.



Model technical data

1	Used for squeezing operations after dyeing and washing of fabrics.
2	It has horizontally arranged cylinders 350 mm or 500 mm wide.
3	The cylinder hardness is 70 shore.
4	Fabric passage speed can be set between 1 and 40 m/min.
5	Squeezing pressure can be set between 2 and 6 bar.
6	A balance adjustment system provides equal pressure.
7	Safety locks are fitted between the rollers.

Physical specifications and utilities

Electrical supply	Approx. 220–240 V AC, 50/60 Hz, single phase; build-dependent.
Power / connected load	Approx. 400–1000 W connected load for preliminary planning.
Overall instrument dimensions	Approx. 1000 × 650 × 800 mm (W × D × H).
Instrument weight	Approx. 120–220 kg net.
Gross / shipping weight	Approx. 157–300 kg gross; estimated packing allowance.
Lab requirements	Dry filtered compressed air if the pneumatic circuit is fitted; operating pressure and flow confirmed at delivery.

Dimension order and approximate values are stated in each row. Packaging data are separate from instrument dimensions and net mass. Approx. rows are preliminary engineering estimates based on comparable equipment and function/capacity; they are not verified manufacturing measurements or standard requirements. Installation and shipment are finalised against the approved drawing and nameplate. Estimate scope: base product / one unit; external computer, bench and auxiliary plant excluded.

Specifications, dimensions, and power requirements are approximate and subject to change without prior notice for continuous design improvements.

Product technical specifications and images may vary according to manufacturing conditions and applicable standards.

Test and configuration

Measured output / function	Wet pick-up after impregnation and squeezing (%)
Parameters selected for the method	Roller pressure, feed speed and fabric width
Verification points	Roller parallelism, pressure and speed

Control and recording specification

Method-specific software and recording requirements follow. Delivered software modules are defined by the order scope.

- Method code and edition, specimen ID, operator and selected test parameters are linked to the record.
- The calculation and endpoint are defined by the selected method edition; instrument signals and operator assessments are kept distinct.
- Raw measurements, units, valid/invalid test flags and the reported result remain traceable.
- Calculations are checked against known inputs and an independent calculation; sensor channels are checked against calibration values.

Related test methods

-

Listed methods are application references. Suitability is established by assessing hardware, method edition and calibration together.